

Seismic network and monitoring in Taiwan

Nai-Chi Hsiao* and
Tzay-Chyn Shin
Central Weather Bureau (CWB), Taiwan

January 16, 2013










Outline

- Introduction of the real-time seismic network in Taiwan
- **Operations for seismic monitoring**
 - Earthquake catalog publish
 - Earthquake rapid reporting
 - Earthquake early warning



CWBSN

Central Weather Bureau Seismic Network




Tasks:

- Earthquake catalog
- Earthquake rapid notification and early warning
- Tsunami warning
- Seismological related research

TSMIP

Taiwan Strong Motion Instrumentation Program network




Tasks:

- Strong-motion database
- Strong-motion seismology research
- Earthquake engineering application

TGNS

Taiwan Geophysical Network for Seismology



Tasks:

- Geophysical database
- Earthquake precursor study
- Crustal deformation and active fault monitoring










CWBSN framework

138 stations totally



- Integrate and upgrade all of Taiwan's short-period stations in 1991. Add strongmotion seismometers in stations in 1995.
- The main seismic stations for earthquake observation in Taiwan for the past 20 years.
- Totally upgrade the resolution to 24 bits in 2012.
- 70 stations established.















Broadband station

- Start to build the stations and install broadband seismometers in 2001.
- High quality and resolution data are acquired for seismological related research.
- 29 stations established.






- Start to build the stations in 2007 in order to establish the next generation of seismic station in Taiwan.
- Borehole depth is set to 300 meter.
- 3 seismometers are installed in a station, include 1 borehole broadband sensor, 1 borehole FBA sensor, and 1 surface FBA sensor.
- 30 stations established, and plan to build 70 stations totally for the next few years.





Downhole station framework









2010/3/4 8:18:52 M_L 6.4

Toucheng station




OBS station

- 1 cable based OBS station is constructed off northeastern Taiwan in 2011 to improve the capabilities of earthquake monitoring.
- Cable laid from Toucheng, Yilan county. The cable length is about 45 km, and the water depth of station is about 300 meter.
- 1 broadband sensor and 1
 FBA sensor are installed.
- Plan to extend the cable length and add more OBS in the future.











OBS waveform

2012/8/31 12:47 M_w 7.6







Processing program


(D.-Y. Chen)



Multi-channel waveform

2010/3/4 16:16:16 M₁ 5.7

Lanyu station






- Earthquake catalog publish
- Earthquake rapid reporting
- Earthquake early warning




Taiwan earthquake catalog





Seismicity observation


Measurement the seismicity changes by values a and b




(C.-H. Chang)



Seismogenic structure study





(C.-H. Chang)











Earthquake rapid notification





Latitude (N)

Depth (Km)

119.0

Earthquake report statistics 431 382 Earthquake Number 26.0 300 2006~2012 984 Events 200 25.0 (2006/1~2012/12) 123 Earthquake 100 Difference related to catalog 25 24.0 2 - 3 3 - 4 > 7 ML 0.5 23.0 STD x 0.5 0.4 0.β5 0.85 22.0 M_L Deviation 0|3 0.3 $5.08 \pm 6.21 \text{ km}$ 0.27 Epicenter deviation: 5.08 +- 6.21 km 21.0 -30 -60 -90-120-150 Depth (Km) 0.1 Depth deviation : 4.73 +- 5.64 km 4.73 ± 5.64 -150

120.0

121.0

Longitude (E)

122.0

123.0

2006


2007 2008

Year

2009 2010 2011 2012





Reporting time






Virtual Sub-Network for EEW








EEW Capability







Promotion plan for EEW in Taiwan

- For promoting and testing the EEW application in Taiwan, a joint program in cooperation with CWB and National Science and Technology Center for Disaster Reduction (NCDR) was performed.
- Currently, the organizations of application include elementary schools, power plants, transportation networks, and disaster prevention agencies.








Message disseminative platform


- Internet as the main medium
- Active platform
- Client-server architecture






Transmission test

Using the Radio Data System



Using Low-Frequency Time and Frequency Broadcasting System



Application of EEW to Schools

Regional and onsite EEW message was linked with the broadcasting system to automatically inform teachers and students at 4 schools with collaboration of NCDR, NCREE, and CWB.

Metropolitan area


Fanghe junior high school, Taipei

High seismicity area

> Yilan elementary school, Yilan

High earthquake potential area

National Chungcheng University, Chiayi Gangping elementary school, Chiayi





Activate emergency responses

LED display and broadcasting

in classrooms




Application of EEW


- Pilot test at Emergency Response Center
 - ➤ EEW message was received via internet at National Fire Agency for testing with collaboration of NCDR, CWB, and NCHC.



➤ Customized EEW message was sent by CWB to THSR for testing and pilot application with collaboration of CWB, NCDR, and NCREE.




EEW received via internet



EEW message for Taiwan High
Speed Rail
Seismological Center, Central Weather Bureau

Advanced EEW procedure developed




 $M_{\tau c} = 4.218 * log10(\tau_c) + 6.166$

(Wu et al., 2010)

 $M_{Pd} = 3.905 + 2.198 * log10(Pd) + 2.703 * log10(R) (Hsiao et al., 2010)$


(D.-Y. Chen)

Example





20120226023527_n26.rep Mpd=6.23, Mtc=6.32, Time=27.05











The End

Thank you for your attention!

